

Cambridge X37NST

Deliver engaging instruction and brilliant projected images—without breaking your budget. Image adjustment features make the X37NST short-throw projector the perfect replacement for interactive technology you already own.



Features

- 3,700 lumens, short throw 0.46:1
- Multiple inputs, including 2 HDMI ports
- USB display for PC-less presentation
- Keystone correction: H/V, Auto, 4-Corner, Pincushion, Barrel

Specifications

Display	
Brightness	3,700 lumens (2,600 eco)
Light Source	218W Phillips, low-pressure mercury vapor
Lamp Life (typical)	4,000 hrs. (standard); 10,000 hrs. (eco)
Native Aspect Ratio	4:3 (standard); 16:10 (compatible)
Native Resolution	XGA 1,024 x 768
Supported Resolution	Up to WUXGA 1,920 x 1,200
Image Size (diagonal)	50 in. ~ 100 in. / .455 m ~ .943 m
Keystone Correction	V: $\pm 15^\circ$ (auto and manual) H: $\pm 15^\circ$ (manual) Pincushion/Barrel Correction Corner Keystone
Contrast Ratio (typical)	10,000:1 (with IRIS and eco mode)
Color Reproduction	1.07 billion
Color Uniformity	80%
Projection Lens	f=1.8
Projection Lens	f=6.08mm
Zoom Ratio	N/A
Throw Ratio	0.46:1
Focus Type	Manual
Projection Technology	3 x 0.63 in. LCD (Liquid Crystal Display)

Closed Captioning	CC1, CC2, CC3, CC4
Audio/Video Connections	
Digital A/V Inputs	<ul style="list-style-type: none"> - HDMI x 2 (1 x MHL) Mobile High-Definition Link - USB-A <ol style="list-style-type: none"> 1. Memory card viewer 2. Wi-Fi dongle (optional accessory) - USB-B - LAN x 1 (also control)
Video Analog Inputs	<ul style="list-style-type: none"> - VGA x 1 (also YCbCr/component, S-Video) - VGA x 1 (switched in/out) - Video x 1
Video Analog Outputs	<ul style="list-style-type: none"> - VGA x 1 (switched in/out)
Audio Analog Inputs	<ul style="list-style-type: none"> - RCA L/R (mono) x 1 - 3.5mm x 1
Audio Analog Outputs	<ul style="list-style-type: none"> - 3.5mm x 1
Speaker	10 W x 1
Control	
Control	<ul style="list-style-type: none"> - RJ45 x 1 (shared with video) - RS-232C
LAN Control Protocols	<ul style="list-style-type: none"> - Crestron RoomView - AMX Discovery - PJ Link
Service/Network	USB-B x 1 (shared with video)
Mechanical	
Mounting	Table/ceiling, front/rear
Security	<ul style="list-style-type: none"> - Security bar - Password - Control panel lock - Kensington lock
General	
Power Supply	100~240V @ 50/60Hz
Power Consumption	<ul style="list-style-type: none"> - 270 W (typical) - <0.5 W (eco standby) - <3 W (network standby)

Fan Noise Max	34.9dB (eco) 38.9dB (normal)
Lamp Access	Top
Filter Access	Side
Environmental	
Operating Temperature	0°C ~ 40°C (35°C ~ eco)
Storage Temperature	-20°C ~ 60°C
Operating Humidity	20% ~ 85%
Storage Humidity	10% ~ 85%
Dimensions and Weight	
Product Dimensions	347 mm x 341 mm x 142 mm (13.66 in. x 10.43 in. x 5.6 in.)
Net Weight	4 kg (8.8 lbs.)
Packaged Dimensions	463 mm x 458 mm x 211 mm (18.2 in. x 18.1 in. x 8.3 in.)
Gross Weight	5 kg (12.1 lbs.)
Safety	
Certifications	TUV, CE, CB, FCC
Accessories	
Included Accessories	<ul style="list-style-type: none"> - CD user manual - Quick Start Guide - 2 M Power cord - 3 M HDMI - Remote (with batteries)

What's in the box

Hardware

- Remote control with batteries

Documentation

- Warranty card
- QuickStart Guide
- CD User manual

Cables

- HDMI cable (2 m)
- US power cord (3 m)

Options

- Lamps for Life
- ALLIN1-980 universal ceiling mount
- USB-Wi-Fi wireless USB adapter

Specifications are subject to change without notice.

Drawings

