

# N12BNW Projector



## Package Contents

**N12BNW non-interactive projector** - Projector, AC power cord (4m), HDMI cable (5m), remote control with battery, and mini-USB cable (5m).

## Specifications

<b>OS</b>	Software Requirements	MimioStudio 11.6 or higher on a Windows, Mac, or Linux OS	
	<b>Display</b>	Brightness	4,000 lumens (2,800 eco)
		Light Source	260 W Philips halogen
		Lamp Life (typical)	3500 hr (standard) / 4000 hr (eco)
		Native Aspect Ratio	16:10
		Native Resolution	WXGA 1280 x 800
		Image Size (diagonal)	80 in. - 110 in. / 203 cm - 279 cm
		Keystone Correction	Vertical: $\pm 10^\circ$
		Contrast Ratio (typical)	1,800:1 (10,000:1 high contrast)
		Color Reproduction	1.07 billion colors (R/G/B 10 bit)
		Color Uniformity	$\Delta u'v' \leq 0.03$
		Projection Lens	f/2.4
		Throw Ratio	Ultra-short throw of 0.27
		Focus Type	Manual
		Projection Technology	Digital Light Processing (DLP), utilizing a 6-segment color wheel.
On Screen Display	Supports English and French		
Closed Captioning	Based on TI DDP4421 spec, CC1/CC2/CC3/CC4 supported		
3D	DLP Link 3D and HDMI 1.4a 3D		
<b>Audio/Video Connections</b>	Digital A/V Inputs	HDMI x 2	
	Video Analog Inputs	- VGA x 1 - VGA in/out switched* x 1 - Composite x 1	
	Video Analog Outputs	VGA in/out switched x 1	
	Audio Analog Inputs	- Stereo line 3.5 mm x 1 - Stereo line RCA jacks x 1 - Mic level 3.5 mm x 1	
	Audio Analog Outputs	Line out 3.5 mm x 1	
	Speaker	1 speaker 10 Watts.	
<b>Control</b>	LAN	Standard using RJ-45 connector	
	LAN Control Protocols	Crestron	
	Laser Curtain DC Power	3.5 mm	
	Service and Network Ctrl	RS-232, RJ45, mini-USB	
<b>Mech</b>	Mounting	Front or rear projection, wall, ceiling, or table mount**	
	Security	Kensington Lock >20 kg	



<b>General</b>	Power Supply	AC 100 – 240 V 50-60 Hz
	Power Consumption (typical)	Normal mode: 330 W ECO mode: 210 W Standby: < 0.5 W Touch Mode***
	Operating Temperature	5 - 40° C (41 - 104° F) non-condensing
	Fan Noise	Full mode : 36dBA (typical) / 38dBA (maximum) ECO mode : 32dBA (typical) / 35dBA (maximum)
	Certifications	UL and FCC

\* One connector switchable between VGA in or out.  
\*\* Ceiling and table mount require third-party bracket.  
\*\*\* LAN/RS-232/VGA out are off.


## Dimensions and Weight

### Projector

Weight: 5 kg  
(11.02 lb)



## Connections



[mimio.boxlight.com](http://mimio.boxlight.com)

To learn more, call 360.464.2119

Specifications subject to change without notice.